



TELEPHONE CABLES

Finolex Telephone cables with high density polyethelene insulated, solid annealed high conductivity bare copper with DIA 0.5mm, paired, polyester taped and sheathed with high oxygen index Fire Retardent PVC compound, generally conforming to ITD specifications G / WIR-06/02. May 94 and Finolex specifications.

**Product Code	Type	LP per 90 Mtr Rs.	Packing
31050013	1 pair	555	Standard length of the coil is 90 Mtrs.
31050023	2 pair	960	
31050033	3 pair	1415	
31050043	4 pair	1855	
31050053	5 pair	2310	
31050103	10 pair	4470	
31050203	20 pair	8355	
31050503	50 pair	20215	Standard length of the drum is 500m +/-10%
31051001	100 pair	39310	

Finolex Telephone cables with high density polyethelene insulated, solid annealed high conductivity bare copper with DIA 0.4 mm, paired, polyester taped and sheathed with high oxygen index Fire Retardent PVC compound, generally conforming to ITD specifications G / WIR-06/02. May 94 and Finolex specifications.

**Product Code	Type	LP per 90 Mtr Rs.	Packing
31040013	1 pair	405	Standard length of the coil is 90 Mtrs.
31040023	2 pair	680	
31040033	3 pair	1000	
31040043	4 pair	1255	
31040053	5 pair	1540	
31040103	10 pair	3090	
31040203	20 pair	5660	
31040503	50 pair	13580	Standard length of the drum is 500m +/-10%
31041001	100 pair	25555	

A nylon ripcord is provided for slitting the jacket without damaging the insulated cores. The outersheath colour is Grey.
For any other pairage please refer to Marketing Department.

NOTES :	
	The items marked as * are Non-Stock items. Please refer to Marketing Department for delivery confirmation indicating quantity, packing length, colour etc.
1. PRICES	GST extra as applicable.
2. PACKING	Available in 90 M coils for 1P to 20P Cables. 50 P cables available in 500m +/-10%
3. PRINTING	Cables are printed with Company Name, Logo, Type .
4. ALTERATION	This Price List supersedes all our earlier price lists and is subject to change without notice.

